

RADIAL PLY TIRES FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE

TIRES MOUNTED ON 15° DROP CENTER RIMS

TIRE SIZE DESIGNATION	USAGE	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES											
		kPa <i>psi</i>	480 70	520 75	550 80	590 85	620 90	660 95	690 100	720 105	760 110	790 115	830 120
10R22.5	DUAL	kg <i>lbs</i>	1750 3860	1830 4045	1910 4230	2000(E) ¹³² 4410(E) ¹³²	2080 4585	2160 4760	2240(F) ¹³⁶ 4940(F) ¹³⁶	2300 5075	2360 5210	2430(G) ¹³⁹ 5355(G) ¹³⁹	
	SINGLE	kg <i>lbs</i>	1850 4080	1940 4280	2030 4480	2120(E) ¹³⁴ 4675(E) ¹³⁴	2200 4850	2280 5025	2360(F) ¹³⁸ 5205(F) ¹³⁸	2430 5360	2500 5515	2575(G) ¹⁴¹ 5675(G) ¹⁴¹	
11R22.5	DUAL	kg <i>lbs</i>	1990 4380	2080 4580	2160 4760	2250 4950	2360(F) ¹³⁸ 5205(F) ¹³⁸	2460 5415	2560 5625	2650(G) ¹⁴² 5840(G) ¹⁴²	2680 5895	2710 5950	2725(H) ¹⁴³ 6005(H) ¹⁴³
	SINGLE	kg <i>lbs</i>	2050 4530	2160 4770	2260 4990	2370 5220	2500(F) ¹⁴⁰ 5510(F) ¹⁴⁰	2600 5730	2700 5950	2800(G) ¹⁴⁴ 6175(G) ¹⁴⁴	2870 6320	2940 6465	3000(H) ¹⁴⁶ 6610(H) ¹⁴⁶
12R22.5	DUAL	kg <i>lbs</i>	2170 4780	2260 4990	2350 5190	2440 5390	2575(F) ¹⁴¹ 5675(F) ¹⁴¹	2630 5785	2680 5895	2725(G) ¹⁴³ 6005(G) ¹⁴³	2840 6265	2960 6525	3075(H) ¹⁴⁷ 6780(H) ¹⁴⁷
	SINGLE	kg <i>lbs</i>	2240 4940	2360 5200	2470 5450	2580 5690	2725(F) ¹⁴³ 6005(F) ¹⁴³	2820 6205	2910 6405	3000(G) ¹⁴⁶ 6610(G) ¹⁴⁶	3120 6870	3240 7130	3350(H) ¹⁵⁰ 7390(H) ¹⁵⁰
11R24.5	DUAL	kg <i>lbs</i>	2110 4660	2210 4870	2300 5070	2390 5260	2500(F) ¹⁴⁰ 5510(F) ¹⁴⁰	2580 5675	2660 5840	2725(G) ¹⁴³ 6005(G) ¹⁴³	2820 6205	2910 6405	3000(H) ¹⁴⁶ 6610(H) ¹⁴⁶
	SINGLE	kg <i>lbs</i>	2190 4820	2300 5070	2410 5310	2520 5550	2650(F) ¹⁴² 5840(F) ¹⁴²	2770 6095	2890 6350	3000(G) ¹⁴⁶ 6610(G) ¹⁴⁶	3080 6790	3160 6970	3250(H) ¹⁴⁹ 7160(H) ¹⁴⁹

NOTES 1: Letters in parentheses denote Load Range for which bold face loads are maximum. International Load Index numbers are shown after Load Range.

IMPORTANT - ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS FOR DIAMETERS AND CONTOURS.