

RADIAL PLY METRIC TIRES FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE

TIRES MOUNTED ON 15° DROP CENTER RIMS

TIRE SIZE DESIGNATION	USAGE	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES														
		kPa Psi	450 65	480 70	520 75	550 80	590 85	620 90	660 95	690 100	720 105	760 110	790 115	830 120	860 125	890 130
215/75R17.5	DUAL	kg lbs				1450 3195	1520 3350	1590 3500	1650 3645	1720 3795	1790 3945	1860 4095	1910 4220	1990 4390	2060(H) 4540(H) ¹³³	
	SINGLE	kg lbs				1530 3375	1610 3540	1680 3695	1750 3860	1820 4010	1900 4180	1960 4330	2040 4495	2110 4650	2180(H) 4805(H) ¹³⁵	
225/70R19.5	DUAL	kg lbs	1180(D) 2600(D) ¹¹⁴	1230 2720	1300 2860	1360(E) 3000(E) ¹¹⁹	1410 3115	1470 3245	1550(F) 3415(F) ¹²³							
	SINGLE	kg lbs	1250(D) 2755(D) ¹¹⁶	1310 2895	1380 3040	1450(E) 3195(E) ¹²¹	1500 3315	1570 3450	1650(F) 3640(F) ¹²⁵							
245/70R19.5	DUAL	kg lbs				1550 3415	1590 3515	1660 3655	1750(F) 3860(F) ¹²⁷	1790 3940	1850 4075	1950(G) 4300(G) ¹³¹				
	SINGLE	kg lbs				1650 3640	1700 3740	1770 3890	1850(F) 4080(F) ¹²⁹	1900 4190	1970 4335	2060(G) 4540(G) ¹³³				
255/70R22.5	DUAL	kg lbs				1800 3970	1860 4110	1940 4275	2000 4410	2020 4455	2090 4610	2120(G) 4675(G) ¹³⁴	2230 4915	2300(H) 5070(H) ¹³⁷		
	SINGLE	kg lbs				1900 4190	1980 4370	2060 4550	2120 4675	2220 4895	2300 5065	2360(G) 5205(G) ¹³⁸	2450 5400	2500(H) 5510(H) ¹⁴⁰		
295/75R22.5	DUAL	kg lbs		1860 4095	1950 4300	2060 4540	2130 4690	2220 4885	2300(F) 5070(F) ¹³⁷	2390 5260	2470 5440	2575(G) 5675(G) ¹⁴¹	2630 5795	2725(H) 6005(H) ¹⁴³		
	SINGLE	kg lbs		2040 4500	2140 4725	2240 4940	2340 5155	2440 5370	2500(F) 5510(F) ¹⁴⁰	2620 5780	2710 5980	2800(G) 6175(G) ¹⁴⁴	2890 6370	3000(H) 6610(H) ¹⁴⁶		
285/75R24.5	DUAL	kg lbs		1870 4135	1970 4340	2060 4540	2150 4740	2240 4930	2360(F) 5205(F) ¹³⁸	2410 5310	2490 5495	2575(G) 5675(G) ¹⁴¹	2660 5860	2800(H) 6175(H) ¹⁴⁴		
	SINGLE	kg lbs		2060 4545	2160 4770	2240 4940	2360 5210	2460 5420	2575(F) 5675(F) ¹⁴¹	2650 5835	2740 6040	2800(G) 6175(G) ¹⁴⁴	2920 6440	3075(H) 6780(H) ¹⁴⁷		

NOTES 1: Letters in parentheses denote Load Range for which bold face loads are maximum. International Load Index numbers are shown after Load Range.
 IMPORTANT - ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS FOR DIAMETERS AND CONTOURS.