

# RADIAL PLY METRIC TIRES FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE

## TIRES MOUNTED ON 15° DROP CENTER RIMS

TIRE SIZE DESIGNATION	USAGE	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES													
		kPa <i>psi</i>	480 70	520 75	550 80	590 85	620 90	660 95	690 100	720 105	760 110	790 115	830 120	860 125	900 130
315/80R22.5	DUAL	kg			2575	2650	2750	<b>2900(G)</b> <sup>145</sup>	2970	3070	<b>3150(H)</b> <sup>148</sup>	3270	<b>3450(J)</b> <sup>151</sup>	3600	<b>3750(L)</b> <sup>154</sup>
	<i>lbs</i>			5675	5840	6070	<b>6395(G)</b> <sup>145</sup>	6545	6770	<b>6940(H)</b> <sup>148</sup>	7210	<b>7610(J)</b> <sup>151</sup>	7940	<b>8270(L)</b> <sup>154</sup>	
315/80R22.5	SINGLE	kg			2800	2910	3030	<b>3150(G)</b> <sup>148</sup>	3260	3370	<b>3450(H)</b> <sup>151</sup>	3590	<b>3750(J)</b> <sup>154</sup>	4190	<b>4625(L)</b> <sup>161</sup>
	<i>lbs</i>				6175	6415	6670	<b>6940(G)</b> <sup>148</sup>	7190	7440	<b>7610(H)</b> <sup>151</sup>	7920	<b>8270(J)</b> <sup>154</sup>	9240	<b>10200(L)</b> <sup>161</sup>

NOTES 1: Letters in parentheses denote Load Range for which bold face loads are maximum. International Load Index numbers are shown after Load Range.  
 IMPORTANT - ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS FOR DIAMETERS AND CONTOURS.