

INFLATION AND LOAD LIMITS FOR RADIAL TRUCK TIRES RATED FOR SPEEDS OF 65 mph or 75 mph

The minimum cold inflation pressure and maximum service load must comply with the following limitations:

OPERATING SPEED RANGE (MPH)	CONVENTIONAL RADIAL				OPERATING SPEED RANGE (MPH)	WIDE-BASE/METRIC RADIAL			
	RATED 65 MPH		RATED 75 MPH			RATED 65 MPH		RATED 75 MPH	
	INFL. PRESSURE CHANGE	LOAD CHANGE	INFL. PRESSURE CHANGE	LOAD CHANGE		INFL. PRESSURE CHANGE	LOAD CHANGE	INFL. PRESSURE CHANGE	LOAD CHANGE
71 thru 75	+5 PSI	-12%	None	None	71 thru 75	+5 PSI	-12%	None	None
66 thru 70	+5 PSI	-4%	None	None	66 thru 70	+5 PSI	-4%	None	None
51 thru 65	None	None	None	None	51 thru 65	None	None	None	None
41 thru 50	None	+9%	None	+9%	41 thru 50	None	+7%	None	+7%
31 thru 40	None	+16%	None	+16%	31 thru 40	None	+9%	None	+9%
21 thru 30	+10 PSI	+24%	+10 PSI	+24%	21 thru 30	+10 PSI	+12%	+10 PSI	+12%
11 thru 20	+15 PSI	+32%	+15 PSI	+32%	11 thru 20	+15 PSI	+17%	+15 PSI	+17%
6 thru 10	+30 PSI	+60%	+30 PSI	+60%	6 thru 10*	+20 PSI	+25%	+20 PSI	+25%
2.6 thru 5	+30 PSI	+85%	+30 PSI	+85%	2.6 thru 5*	+20 PSI	+45%	+20 PSI	+45%
Creep thru 2.5	+30 PSI	+115%	+30 PSI	+115%	Creep thru 2.5*	+20 PSI	+55%	+20 PSI	+55%
Creep**	+40 PSI	+140%	+40 PSI	+140%	Creep** *	+30 PSI	+75%	+30 PSI	+75%
Stationary	+40 PSI	+185%	+40 PSI	+185%	Stationary*	+30 PSI	+105%	+30 PSI	+105%

Creep** Motion for not over 200 feet in a 30-minute period.

* Apply these increases to Dual Loads and inflation Pressures.