

# METRIC WIDE BASE RADIAL TIRES FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE

## TIRES USED AS SINGLES MOUNTED ON 15° DROP CENTER RIMS

TIRE SIZE DESIGNATION	USAGE	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES													
		kPa	480	520	550	590	620	660	690	720	760	790	830	860	900
		psi	70	75	80	85	90	95	100	105	110	115	120	125	130
385/65R22.5	SINGLE	kg	2880	3060	3150	3350	3470	3650	3740	3850	4000	4100	<b>4250(J)</b> <sup>158</sup>		
		lbs	6380	6720	6940	7350	7650	8050	8230	8510	8820	9050	<b>9370(J)</b> <sup>158</sup>		
425/65R22.5	SINGLE	kg	3430	3640	3750	3980	4130	4250	4440	4580	<b>4750(J)</b> <sup>162</sup>	4880	5000	<b>5180(L)</b> <sup>165</sup>	
		lbs	7590	7990	8270	8740	9100	9370	9790	10100	<b>10500(J)</b> <sup>162</sup>	10700	11000	<b>11400(L)</b> <sup>165</sup>	

NOTES 1: Letters in parentheses denote Load Range for which bold face loads are maximum. International Load Index numbers are shown after Load Range.  
 IMPORTANT - ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS FOR DIAMETERS AND CONTOURS.